

## APPENDIX B

Citation from 49 CFR 173

Published 2004

Access via WWW at

<http://www.access.gpo.gov/nara/cfr/cfr-table-search.html#page1>

## Sec. 173.120 Class 3--Definitions.

(a) **Flammable liquid.** For the purpose of this subchapter, a flammable liquid (Class 3) means a liquid having a flash point of not more than 60.5 [deg]C (141 [deg]F), or any material in a liquid phase with a flash point at or above 37.8 [deg]C (100 [deg]F) that is intentionally heated and offered for transportation or transported at or above its flash point in a bulk packaging, with the following exceptions:

(1) Any liquid meeting one of the definitions specified in Sec. 173.115.

(2) Any mixture having one or more components with a flash point of 60.5 [deg]C (141 [deg]F) or higher, that make up at least 99 percent of the total volume of the mixture, if the mixture is not offered for transportation or transported at or above its flash point.

(3) Any liquid with a flash point greater than 35 [deg]C (95 [deg]F) that does not sustain combustion according to ASTM D 4206 (IBR, see Sec. 171.7 of this subchapter) or the procedure in appendix H of this part.

(4) Any liquid with a flash point greater than 35 [deg]C (95 [deg]F) and with a fire point greater than 100 [deg]C (212 [deg]F) according to ISO 2592 (IBR, see Sec. 171.7 of this subchapter).

(5) Any liquid with a flash point greater than 35 [deg]C (95 [deg]F) which is in a water-miscible solution with a water content of more than 90 percent by mass.

(b) **Combustible liquid.** (1) For the purpose of this subchapter, a combustible liquid means any liquid that does not meet the definition of

any other hazard class specified in this subchapter and has a flash point above 60.5 [deg]C (141 [deg]F) and below 93 [deg]C (200 [deg]F).

(2) A flammable liquid with a flash point at or above 38 [deg]C (100 [deg]F) that does not meet the definition of any other hazard class may be reclassified as a combustible liquid. This provision does not apply to transportation by vessel or aircraft, except where other means of transportation is impracticable. An elevated temperature material that meets the definition of a Class 3 material because it is intentionally heated and offered for transportation or transported at or above its flash point may not be reclassified as a combustible liquid.

(3) A combustible liquid that does not sustain combustion is not subject to the requirements of this subchapter as a combustible liquid. Either the test method specified in ASTM D 4206 or the procedure in appendix H of this part may be used to determine if a material sustains

Attorney Docket No.: 00306-00142

combustion when heated under test conditions and exposed to an external source of flame.

(c) Flash point. (1) Flash point means the minimum temperature at which a liquid gives off vapor within a test vessel in sufficient concentration to form an ignitable mixture with air near the surface of the liquid. It shall be determined as follows:

(i) For a homogeneous, single-phase, liquid having a viscosity less than 45 S.U.S. at 38 [deg]C (100 [deg]F) that does not form a surface film while under test, one of the following test procedures shall be used:

(A) Standard Method of Test for Flash Point by Tag Closed Tester, (ASTM D 56);

(B) Standard Methods of Test for Flash Point of Liquids by Setaflash Closed Tester, (ASTM D 3278); or

(C) Standard Test Methods for Flash Point by Small Scale Closed Tester, (ASTM D 3828).

(ii) For a liquid other than one meeting all of the criteria of paragraph (c)(1)(i) of this section, one of the following test procedures shall be used:

(A) Standard Method of Test for Flash Point by Pensky--Martens Closed Tester, (ASTM D 93). For cutback asphalt, use Method B of ASTM D 93 or alternate tests authorized in this standard; or

(B) Standard Methods of Test for Flash Point of Liquids by Setaflash Closed Tester (ASTM D 3278).

(2) For a liquid that is a mixture of compounds that have different volatility and flash points, its flash point shall be determined as specified in

[[Page 488]]

paragraph (c)(1) of this section, on the material in the form in which it is to be shipped. If it is determined by this test that the flash point is higher than -7 [deg]C (20 [deg]F) a second test shall be made as follows: a portion of the mixture shall be placed in an open beaker (or similar container) of such dimensions that the height of the liquid can be adjusted so that the ratio of the volume of the liquid to the exposed surface area is 6 to one. The liquid shall be allowed to evaporate under ambient pressure and temperature (20 to 25 [deg]C (68 to

77 [deg]F)) for a period of 4 hours or until 10 percent by volume has evaporated, whichever comes first. A flash point is then run on a portion of the liquid remaining in the evaporation container and the lower of the two flash points shall be the flash point of the material.

(3) For flash point determinations by Setaflash closed tester, the glass syringe specified need not be used as the method of measurement of the test sample if a minimum quantity of 2 mL (0.1 ounce) is assured in the test cup.

(d) If experience or other data indicate that the hazard of a material is greater or less than indicated by the criteria specified in paragraphs (a) and (b) of this section, the Associate Administrator may revise the classification or make the material subject or not subject to the requirements of parts 170-189 of this subchapter.

Attorney Docket No.: 00306-00142

[Amdt. 173-224, 55 FR 52634 Dec. 21, 1990, as amended by Amdt. 173-227, 56 FR 49989, Oct. 2, 1991; 56 FR 66268, Dec. 20, 1991; 57 FR 45461, Oct. 1, 1992; Amdt. 173-241, 59 FR 67506, 67507, Dec. 29, 1994; Amdt. 173-255, 61 FR 50625, Sept. 26, 1996; Amdt. 173-261, 62 FR 24731, May 6, 1997; 66 FR 45379, 45381, Aug. 28, 2001; 68 FR 75743, Dec. 31, 2003]